HIGH DENSITY SIGNAL & POWER MINIATURIZATION

4 to 24 CONTACTS

- Up to 45% smaller
- Lightweight
- IP68 mated and unmated
- Rugged with high corrosion resistance





H⊃MI™












1:1 SIZE COMPARISON

BODY STYLES





Up to 45% smaller



All dimensions shown are in millimeters and are for reference only.

PLUGS

CABLE MOUNTED







	_	•	
BODY STYLES	S MP11-L	MP11-S	MP11-Q
Locking system	Push-pull	Screw-locking	Quick-release
Sealing up to	IP68	IP68	IP68
Design	Short/Overmolding	Short/Overmolding	Short/Overmolding

RECEPTACLES

CABLE MOUNTED







BODY STYLES	MR50-L
Locking system	Push-pull
Sealing up to	IP68
Design	Short/Overmolding

Screw-locking IP68

Quick-release IP68 Short/Overmolding Short/Overmolding

PANEL REAR MOUNTED







BODY STYLES MR11-L Push-pull Locking system IP68 Sealing up to Design Front-projecting Solder/PCB Termination

MR11-S Screw-locking **IP68** Front-projecting Solder/PCB

MR11-Q Quick-release **IP68** Front-projecting Solder/PCB

SOFT CAPS

- Sealing caps protect unmated connectors in the field
- Perfectly suit applications where a lightweight, noiseless option is preferred



PC-BOARD **TERMINATION**

- Rigid flex solution available for SMD connectors
- Compatible with signal & power
- Custom design available upon request



CABLE ASSEMBLY SOLUTIONS

Rugged & submersible solutions

Bend relief for easy self-assembly

or angled overmolding





For more information visit www.fischerconnectors.com/minimax

